

J2 TECHNICAL ARTICLE

Number 10

July 26, 1980 March 20, 1980 - rewritten From Octagon Heaven

EARLIER OHC CAR SEAT BACK ADJUSTMENT BRACKETS & SEAT DIMENSIONS

A recent advertisement in an English publication gave insight to the proper mounting of the J2 seats. This plus what other authorities had told me, that the J2 did not have seat rails like the "T" series, fell in perspective. The J2 seat back was held in position by a metal peg on the seat and holes in the floor board. The seat base(s) were held in position by a metal strap. If you need metal straps or pegs,

they are available through W. M. Collingburn. His ad. material is printed on the right side.

On the second page (reverse side), is a drawing of a MG J2 seat.

As to the seat material, it was leather.


As to the seat colors, refer back to technical article No. 6.

The original seat base was a pnematic unit, 3 to 4 inches thick. If anyone has any specifications and dimensions, they would be appreciated.



Wm. M. COLLINGBURN

Manufacturer of M.G. Car Interiors and all traditional Coach Trimming GALLOWFIELDS TRADING ESTATE - RICHMOND NORTH YORKSHIRE DL10 4SU - GREAT BRITAIN Tel. Richmond (0748) 4105



Narrow wing TA and earlier OHC car's seat back adjustment practices.

From Lin Ri- Capityated duty and screws for fluing plate to floor. New floor clate and pegicent experience is an ongoin Prope, Next an ongoinal TA degland floor plate. Zinc plated with fixing screws for plate ED per set (2 begs. 2 plates). Weight 375 gms.



Detail of overhead cam type a adjustment stats based to base plate for seal back adjustment.

Note: The right hand picture is looking up at the bottom of the seats, from the floor.

Note: Wm. M. Collingburn is also a new supplier for the supplier list.

